



Never compromise on quality!



MULTI-PURPOSE SPRAY LUBRICANT

Low Viscosity Spray With Excellent Penetrating & Anti-Corrosion Properties

Technical Data Sheet



INDUSTRIAL ADHESIVES RANGE

Description:

A low viscosity solvent and oil blend giving excellent penetrating, de-watering and lubricating properties. Supplied in aerosol cans with a straw for accurate dispensing.

Uses

MULTI-PURPOSE SPRAY LUBRICANT is a high performance, multi-application fluid which has excellent anti-corrosive properties. It can be used for a wide range of demanding uses for automotive and general engineering.

Suitable for freeing seized fasteners particularly where corrosion is a problem. Also as a general purpose lubricant and cleaner to free tight linkages. Displaces moisture and condensation from material surfaces. Light duty lubricant which can be directed towards hard to access components.

Preparation

Ensure surfaces are clean, dry and grease and oil free.

Application

Attach the straw to the nozzle and aim at the component, keeping the can upright. For seized parts allow to penetrate from all angles for some seconds and progressively loosen adding more lubricant as the threads free.

For stiff linkages remove old grease or dirt and direct the jet onto the linkage until free of old build up, activate linkage to allow full penetration. Reseal with fresh grease for heavy duty applications.

To displace moisture wipe away excess then spray a light coat across all surfaces. Do not spray at hot surfaces or live electrical systems.

Container Size

400ml aerosol tin.

Shelf Life

12 months from date of manufacture, when stored in original, unopened canister. See neck of can for batch reference.

Storage Conditions

Store below +50°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Observe the label precautions. **MULTI-PURPOSE SPRAY LUBRICANT** must be stored in accordance with the flammable liquid storage regulations.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce canister.

Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner.

Health & Safety

Highly flammable. Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Flammability	Highly flammable
Flash Point	-40°C
Boiling Point	140°C
pH	N/A
Solubility in Water	Insoluble
UFI	K470-V0XP-C00X-98SG

Product / Order Details:

Code	Colour	Size	Barcode
BIMP400	Clear	400ml	5060021361363



Part of the Bond It Glues & Adhesives Range



The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



Rev: V4 10/10/22
 Supersedes: V3 16/2/21