

bond it

Never compromise on quality!



AEROSOL SPRAY ADHESIVE

High Strength DCM-Free Aerosol Adhesive

Technical Data Sheet



INDUSTRIAL ADHESIVES RANGE

Description:

A non-chlorinated, exceptionally strong, fast acting, easy to use, multi-purpose adhesive in an aerosol can.

Uses

Bond It **SPRAY ADHESIVE** is a non-chlorinated, exceptionally powerful, long-lasting, multi purpose adhesive. It does not contain damaging or harmful materials such as CFC's or Methylene Chloride (Dichloromethane). For use on materials such as fabrics, wood, concrete, metal, plastic, rubber, paper, card and is particularly suited to bonding foam to foam. It is fitted with a variable discharge nozzle that controls the width of the spray fan; the more pressure applied to the nozzle the wider the fan. It is ideal for the fixing of carpets, carpet tiles, cork tile, underfelts and minor floor installations, for use in the furniture and automotive industries, especially for bonding foam to a variety of surfaces. Also suitable for use in repair and non-structural applications where a high strength bond is required.

Application

SHAKE WELL BEFORE USE. ONLY USE IN WELL VENTILATED AREAS. Ensure surfaces are clean, dry and free from any contaminates that may hinder adhesion. For best results; use in temperatures between +15 and +25°C. Apply to the surface holding the can approx. 25cm away. For a strong bond apply to both surfaces, for a lighter bond apply to only one. Leave the solvent content of the adhesive to evaporate for 3-5 minutes before bringing the surfaces and applying pressure, working outwards from the centre. Excess adhesive is easily removed by using solvent / lighter fluid, etc. When finished; invert the can and spray for a few seconds in order to clear the valve ready for the next use.

Limitations

Not recommended for use on polystyrene or plasticised PVC. Note: This product should not be used for construction purposes such as unsupported head linings in vehicles and boats. It is NOT suitable for use with non rigid / plasticised PVC and should not be used on surfaces where temperatures may exceed +50°C.

Container Size

500ml aerosol can.

Colour

Beige in colour.

Shelf Life

12 months from date of manufacture, when stored in original, unopened containers.

Storage Conditions

Caution: pressurised container. Should be stored between +5 and +25°C in dry areas protected from direct sunlight. Do not expose to temperatures exceeding +50°C. Do not pierce or burn even after use. Do not spray on a naked flame or any incandescent material.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce can.

In the event of spillage remove all sources of ignition, ventilate the area, remove people from confined areas. Material should be mopped up immediately with an inert absorbent material such as sand.

Health & Safety

Highly flammable. Please refer to separate material safety data sheet for full handling, use and storage instructions. If respiratory protection is required use an organic vapour/particulate face mask. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Flammability	Extremely flammable
Appearance	Sticky resin
Solubility in Water	Insoluble
Application Temperature	+15°C to +20°C
Coverage	4m ² per 500ml
UN No:	1950 Aerosols flammable
UFI	UFI: 6X30-M0ER-X00X-GVRW

Product / Order Details:

Code	Colour	Size	Barcode
BDA007	Beige	500ml	5060021361929



Part of the Bond It Glues & Adhesives Range



The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



Rev: V5 10/10/22
 Supersedes: V4 16/8/22